

6 Cube Barrel Blast Heavy Duty



DISA

GOFF

Features

Rotary Scalping Drum

Dual Elevator System

Eye-Level Separator Adjustments

15 HP Direct Drive Blast Wheel

Rubber Mill Belt

Machine Warranty

Quick Cleaning Cycle

Safety Interlocks

Automatic Timer Controls

SPECIFICATIONS—6BBD

EQUIPMENT DIMENSIONS

	6BBD	FMC
Width	10'5"	3'10"
Height	11'6"	6'8"
Length	4'9"	4'5"
Weight	7,000 lbs.	900 lbs.

AIRLESS BLAST UNIT

BLAST WHEEL: The direct drive blast wheel revolves at 3600 RPM for maximum abrasive velocity. 12" diameter wheel with 7 curved blades 3" wide is standard. Balanced wheel components assure smooth operation.

BLADES: Unique snap lock design eases blade replacement. Cast from abrasive resistant alloy to insure maximum life. Curved blade design provides maximum abrasive control.

CONTROL CAGE: Dial type cage.

WHEEL HOUSING: Fabricated from 1/4" wear resistant steel plate. Housing is lined with cast interlocking abrasive resistant liners.

CABINET CONSTRUCTION

CABINET: Pitless type, all welded structurally reinforced cabinet is fabricated from 3/8" steel plate.

POWER LOCK DOOR: Electronically controlled with fingertip action. Pneumatically operated air cylinder provides opening/closing action of power door for full access to blast chamber.

MILL CONSTRUCTION

RUBBER TUMBLE BELT: Continuous molded rubber tumble belt has 4 ply construction with 5/16" abrasive drain holes. Raised rubber tumbling ridges are molded directly to belt.

CONVEYOR ROLLERS: Heavy duty rollers have 2" diameter solid shafts and mounted to the cabinet with standard (4) bolt flange bearings.



DISA Goff, Inc.
One Pleasant Grove Road
PO Box 1607
Seminole, Oklahoma 74818-1607
USA

Tel 405-382-6900
Tel 800-654-4633
Fax 405-382-7013
disagoff@disagoff.com
www.disagoff.com



DISA

THE A. P. MOLLER GROUP

LINERS: 28" diameter barrelheads are 5/8" abrasive resistant steel with special forged retainer bolts. Tight sealing 3/8" alloy steel cabinet liners are standard.

CAPACITY: 6 cu. feet, 800 pounds nominal.

CONVEYOR SPEED: 12 feet per minute.

DRIVE CLUTCH: Damage to the tumble belt and liners, due to internal jamming of parts, is reduced by a torque limiting clutch. A zero speed indicator provides automatic machine shutdown.

BARREL SIZE: 37" wide x 28" diameter.

ABRASIVE RECYCLING SYSTEM

SCREW CONVEYORS: Heavy duty 6" screws with solid shafting are chain and sprocket driven and protected by torque limiting clutch.

ELEVATOR: Centrifugal discharge belt and bucket elevator is dust tight. Quick clamped removable cover permits service and inspection. All shaft bearings are exterior mounted for extended life. Screw adjusted take-up provide positive belt adjustment.

SCREENING: Primary screen in cabinet protects elevator from large objects. A secondary screen in storage hopper provides positive blast wheel protection.

ABRASIVE REQUIRED: 1200 pounds initial.

ABRASIVE CONTROL: Fully adjustable butterfly valve provides precise flow control of abrasive. Totally enclosed design means maximum noise suppression.

SEPARATOR: Double 20" lip separator has adjustable abrasive spreader and adjustable refuse gate for maximum contaminate removal.

VENTILATION ???DISA FMC>???

DUST COLLECTOR:

ELECTRICS

NEMA type 12 electrical enclosure, fusible disconnect switch, thermal overload protection on all motors, 230/460 volt primary, 115 volt secondary control transformer, oil tight push buttons controls. 15 minute abrasive cycle timer. Timer controls for abrasive flow and blast wheel motor. Mill lockout for blast pattern test. Cycle alarm signal and hour meter standard. All motors TEFC, ball bearing, 230/460 volt, 3 phase.

SAFETY FEATURES

Blast wheel operational only when front power door is closed and secure. Automatic power shutdown if internal jamming occurs.

NOISE LEVEL: Approx. 85 DB.

Specifications subject to change without notice.